



Description	Environmental conditions
SB-DN-R0816 Relay Module is a Intelligent Switch output Module which is developed by HDL. RS485 is used for the communication. It has Scene Controller, with Bypass Switch for Manual Control.	Working temperature : -5°C~45°C Working Relative Humidity : 20%~90% Storage temperature : -40°C~+55°C Storage Relative Humidity : 10%~93% IP Class: 2.0
Features	Performance parameters
4 Relay Channels for Output Scene Controller Available Up to 4 separate Area Up to 16 scenes in each Area, maximum running time to each scene is 60 minutes Light Protect Delay time for each channel : 0-60 Minutes Switch on Delay time for each channel: 0-25 seconds Manual control for each channel is available Remote control and management Back to the previous scene or designated scene once system restart RS485 Protocol is used for Communication	Bus Power Supply : DC24-30V Bus Power Consumption : Dynamic Current : 40mA/DC24V Static Current : 15mA/DC24V Lighting Channel : 4 channel Maximum Current in each channel : 16A Relay Life time: > 60000 Capacity Load of Relay Unit : < 300μF Standard 35mm Din Rail Installation 50A magnetic latching relay used CE approved
Installation Dimension	
 <p>Front View</p>	 <p>Side View</p>
Installation Requirements	
For safety , A proper <b>fuse or MCB must be connect to each circuit</b> . The power cable require : 0.2..4 mm² multi- core and 0.4...6 mm² single-core. The tightening torque not exceed 1Nm . Bus connection: Cat5e. Modular installation: DIN-Rail . Mounting position: Electric switch box	

System connection diagram

PC

RJ45

POWER

MBUS011P

MR0410

DIMMER

PANEL

HDL-BUS

Device

Device

Device

Device

Smart-Bus CAT5 Wire Definition

Brown White/ Orange White	COM
Blue White /Green White	DATA-
Blue/Green	DATA+
Brown/ Orange	DC24V

Recommended Connection: Hand in Hand

Wiring For Installation