

Description	Environmental Conditions
SB-DLP-MEU Multifunction LCD panel has many useful function pages: Lighting control , Curtain control , Air Condition control , Floor heating, Back Ground Music, TV etc. It is very easy to program and Operation.	Working Temperature: -5℃~45℃ Operating Relative Humidity: 20%~90% Storage Temperature: -40℃~+55℃ Storage Relative Humidity: 10%~93% Protection Grade : 2.0
Features	Performance Parameter
- IR Function - Multi Key Mode: Single on, Single Off, Single on-off, Combination on, Combination off, Momentary etc. - Multi Control Type: Scene, Sequence, Timer, Universal Switch, Single Channel control, Broadcast Scene, Broadcast channel, curtain function etc. - Page 1-4 are for user customization, Page 5 is for Air Condition & Floor Heating, Page 6 is for Back Ground Music Control. - LED Back Light Adjustable; - Electronic Password Setting;	- Power Input: DC15-30V - Power Consumption : 30mA/DC24V - Installation : GI (3" X3") Back Box - Dimension : 86.4mm×86.4 mm×35mm
Installation Dimension	
Front View Side View Back View	
Installation Requirement	
Standard GI 3" x3" Back Box BUS Interface Connection: CAT-5 UTP	

System Connections Diagram									
	Smart-Bus CAT5 Wire Definition <table> <tr> <td>Brown, White & Orange, White</td><td>For COM</td></tr> <tr> <td>Blue, White & Green, White</td><td>For DATA-</td></tr> <tr> <td>Blue & green</td><td>For DATA+</td></tr> <tr> <td>Brown & Orange</td><td>For DC24V</td></tr> </table>	Brown, White & Orange, White	For COM	Blue, White & Green, White	For DATA-	Blue & green	For DATA+	Brown & Orange	For DC24V
Brown, White & Orange, White	For COM								
Blue, White & Green, White	For DATA-								
Blue & green	For DATA+								
Brown & Orange	For DC24V								
Hand in Hand Connection									
Wiring for installation									
Packing List									
SB-DLP-MEU	1 PC								
Installation Manual	1 PC								
Safety and Maintenance									
Read All Instructions in detail before use Make sure good Ventilation Environment Pay Attention to Water-proof, shake-proof and dust-proof when using Non-Rain, Non-Contact with other liquids or corrosive gases Should be dried in time if invaded by water or liquid Contact Professional maintenance staff or HDL company when Product has problem									